

Lider



Usable Box Dimensions
260 x 155 x 177 cm

Overall dimensions
409 x 206 x 217 cm

Standard DGVW
1350 kg

DGVW on request
1000/1100/1200 kg
1300 kg

Tare weight
480 kg

Axle(x)- Capacity
Single – 1350 kg

Wheels
165R13C

Jockey Wheel
Ø 60

Châssis
Fixed

Timon
Galvanised A frame

Featuers :

- Aerodynamic front-end
- Low-profile chassis
- Welded galvanised chassis
- Inertia brakes
- Height from floor to ground = 35 cm
- Door opening(s) (lxH) = 150 x 175 cm
- Anti-slip interior floor
- Interior walls in CP
- Combined Rear door with ramp as standard)
(max payload 350 kg)
- Interior ceiling light
- Recessed lights
- Rear drop legs
- Lashing rings (x 6 inside)

THE OPTIONS- Equipment options !

DESIGNATION	REF.
Side door 0m60 Factory fitted only	42004
Lashing rail kit 1 rail on each side + 4 lashing rings Factory fitted only	31015
Rail lashing rings (by unit)	12538ASP
Spare Wheel	02055
Spare wheel support (to be fixed inside on reinforcing crossbar front - 3 possible positions: left, right or centre)	42002