

Lider**Key features :**

- Aerodynamic front and top panels formed from a single composite shell
- Low-slung chassis
- Galvanised welded frame
- Height from floor to ground = 35 cm
- Dimensions of the ramp door opening (WxH): 155x169 cm
- Non-slip interior flooring
- Side walls made of FRP Plywood
- Standard rear tailgate (maximum payload 350 kg)
- Interior light
- Recessed lights
- Rear drop stands
- Lashing rings (6 x internal)

OPTIONS :- To customise your trailer!

DESCRIPTION	REF.
Side door Factory fit only	45002
Door opening dimensions (W x H): 60 x 112 cm	
Lashing rail kit	31015
1 rail on each side + 4 lashing rings. Must be fitted at the factory	
Extra rail lashing rings (sold individually)	12538ASP
Ramp door security locking system	42012
60 mm jockey wheel instead of 48 mm Factory fit only	45005
Jockey wheel handle Ø 60	15490
Spare Wheel	02064
Spare wheel mounting bracket (to be fitted on the inside of the front reinforcement cross-member with 3 possible positions: left, right, centre)	45001

Dimensions of load compartment

300*x 160 x 175 cm

* Minimum length

Dimensions overall

453 x 210 x 222 cm

GDVW standard

2000 kg

DGWV on request

1500/1700 kg

Empty weight

620 kg

Axle(x) - load capacity

Double- 2x1100 kg

Wheels

155R13C

JockeyWheel

Ø 60

Chassis

Fixed

Drawbar type

Galvanised A Frame