

x Van – 45960 – 2.60 m – Braked – 1350 Kg

Lider



Dimensions of load compartment

260* x 160 x 175 cm

* Minimum length

Dimensions overall

410 x 208 x 223 cm

GDVW standard

1350 kg

DGVW on request

1000/1100/1200 kg

1300 kg

Empty weight

480 kg

Axle(x) - load capacity

Single –1350 kg

Wheels

165R13C

Jockey wheel

Ø 60

Chassis type

Fixed

Drawbar type

Galvanised A Frame

Key features :

- Aerodynamic front and top panels formed from a single composite shell
- Low-slung chassis
- Galvanised welded frame
- Height from floor to ground = 35 cm
- Dimensions of the ramp door opening (WxH): 155x169 cm
- Non-slip interior flooring
- Side walls made of FRP Plywood
- Standard rear tailgate (maximum payload 350 kg)
- Interior light
- Recessed lights
- Rear drop stands
- Lashing rings (6 x internal)

OPTIONS : - To customise your trailer!

DESCRIPTION

	REF.
Side door Factory fit only	
Door opening dimensions (W x H): 60 x 112 cm	45002
Lashing rail kit	
1 rail on each side + 4 lashing rings. Must be fitted at the factory	31015
Extra rail lashing rings (sold individually)	12538ASP
Ramp door security locking system	42012
60 mm jockey wheel instead of 48 mm Factory fit only	45005
Jockey wheel handle Ø 60	15490
Spare Wheel	02055
Spare wheel mounting bracket (to be fitted on the inside of the front reinforcement cross-member with 3 possible positions: left, right, centre)	45001

Type approval CE

